NOWOŚĆ!

UNIWERSALNY ZBIORNIK LPG O POJEMNOŚCI OD 600 DO 1000 LITRÓW

CHEMET S.A., europejski lider w zakresie urządzeń ciśnieniowych, wprowadza na rynek użytkowników gazu płynnego propan-butan (LPG) zupełnie nową rodzinę uniwersalnych zbiorników, stanowiących połączenie zalet butli gazowej oraz zbiorników stacjonarnych.

Podstawowe dane techniczne:

Zbiorniki są produkowane zgodnie z dyrektywą europejska ciśnieniową TPED 2010/35/WE (spełniają przepisy ADR/RID, EN 14208:2004 oraz EN 13445) oraz oznakowane znakiem П.
Temperatura eksploatacji: -20/+50°C; ciśnienie maksymalne 30 bar.
Tankowania systemem wagowym oraz objętościowym (autocysterna).
Podnoszenie i transportowanie zbiornika napełnionego: dźwigiem; wózkiem widłowym lub wózkiem paletowym.

Zastosowanie

Uniwersalne zbiorniki LPG produkowane przez CHEMET S.A. przeznaczone są do transportu i magazynowania gazu LPG wykorzystywanego głównie w gospodarstwach domowych, obiektach gastronomicznych i usługowych. Nadają się idealnie jako zbiorniki magazynujące gaz, wykorzystywany do celów:

a) gotowania w domu oraz wszelkiego typu obiektach gastronomicznych,
b) podgrzewania ciepłej wody ,
c) instalacji klimatyzacyjnych oraz chłodniczych,
d) instalacji służących w rolnictwie do ekologicznego wypalania chwastów.
e) ogrzewania małych i dogrzewania dużych obiektów budowlanych.
f) tymczasowych oraz sezonowych zastosowań
g) do testowania, serwisowania i w awaryjnych sytuacjach na potrzeby instalacji LPG

Szerokie zastosowanie zbiorniki znajdują również we wszelkiego rodzaju instalacjach, gdzie gaz jest stosowany w celach technologicznych. Przykładem tego są fermy drobiu, suszarnie produktów rolnych czy zakłady produkcyjne.

Konstrukcja:

Podstawowa konstrukcja zbiorników jest zgodna z dyrektywą TPED 2010/35/EC oraz normami zharmonizowanymi. Są one wykonane jako pojemniki poziome o średnicy 800 mm, z blach ze stali węglowej, pokrytej wysokiej jakości powłoką malarską w kolorze białym .

SPECYFIKACJA TECHNICZNA						
Pojemność	m³	0,6	0,7	0,8	0,9	1
Maksymalne napełnenie procentowe	80%					
Maksymalne napelnenie wagowe	kg	252	294	326	378	420
Ciężar pustego zbiornika	kg	317	342	366	390	409
Gabaryty transportowe	mm	H 910 x W 800 x L=				
		1607	1817	2017	2227	2427

www.chemet.com.pl

NOVELTY!

UNIVERSAL LPG TANK – FROM 600 TO 1000 LITERS

CHEMET S.A., the European leader in design and manufacture of pressure equipment, introduces a brand new product family of universal LPG tanks, which combine advantages of both small LPG cylinders and stationary LPG bulk tanks.

Basic Technical Data

Universal tanks are manufactured in accordance with the Transportable Pressure Equipment Directive TPED 2010/35/EC (they meet the requirements of ADR/RID, EN 14208:2004 and EN 13445) and are Π-marked. Operational conditions: temperature: -20°C /+50°C; max. working pressure: 30 bar.

Two ways of refueling: by weight or by volume (from a road tanker).
Lifting and transport of the full tank: crane, forklift truck or pallet truck.

Applications

Universal LPG tanks manufactured by CHEMET SA are designed for transportation and storage of LPG and have been optimized for domestic applications, restaurants, small service and production shops. They are an ideal solution for the following applications:

a) cooking at home and in all types of restaurants,
b) water heating,
c) air-conditioning and refrigeration installations,
d) ecological weed burning in agriculture,
e) small seasonal house heating (huts, cottages),
f) additional heating systems for buildings already equipped with e.g. heating pumps, solar panel etc.,
g) other seasonal or temporary applications,
h) testing, servicing and emergency application at other LPG installations.

The wide scope of applications of the universal tanks can also be found in different installations where LPG is only used for technological purposes, e.g.: at the chicken farms, drying plants for agricultural products.

Design

The basic design of universal tanks conforms the TPED 2010/35/EC and the harmonized standards. They are manufactured as horizontal vessels with 800 mm diameter

TECHNICAL SPECIFICATION						
Volume	m³	0,6	0,7	0,8	0,9	1
Maximum filling	80%					
Maximum filling	kg	252	294	326	378	420
Weight of empty vessel	kg	317	342	366	390	409
Transport dimensions	mm	H 910 x W 800 x L=				
		1607	1817	2017	2227	2427